

### 1.75" Geothermal PTS-CCL

#### Application

The 1.75" Geothermal PTS-CCL tool has an external fast response temperature sensor that is exposed to the wellbore fluid and an internal pressure piezo sensor that senses wellbore pressure through a capillary tube. The casing collar locator (CCL) uses high strength, long life magnets that provide accurate depth correlation when run downhole. It is compatible with the 5" or 7" Fullbore Spinner as well as the 1.375", 1.688" and 2.125" Continuous Spinner.

The temperature sensitive downhole electronics are thermally insulated inside a vacuum flask with a heat sink to reduce the rate of temperature rise within the flask. This allows the 1.75" Geothermal PTS-CCL tool to operate in extreme temperature applications; up to 300°C for 8 hours.

#### Features

- 8 hours @ 300°C (600°F)
- External Fast Response Temperature Probe
- Casing Collar Locator
- Compatible with a Number of Different Flowmeters
- 0.1s Fast Sample Rate Option
- Pressure Trigger Option
- 1.8 Million Sample Capacity
- Inconel 718 - NACE MR0175

#### Benefits

DataCan piezo gauges have excellent efficiency, meaning the battery life of the tool is just as good, if not better than competitors. DataCan piezo gauges have shock mounted electronics which means they have high reliability. DataCan program and download software is industry leading with the fastest graphing package available that is both customizable and easy to use.



### 1.75" Geothermal PTS-CCL

#### 1.75" Geothermal PTS-CCL - Inconel 718

Pressure	Part No.
750 psi	107630
1,500 psi	107631
3,000 psi	107632
6,000 psi	107633
10,000 psi	107634
15,000 psi	107635
20,000 psi	107636

#### Compatible Spinners

Spinner Type	Size	Version	Part No.
Fullbore Spinner	5"	Standard Service	AM005WA0002
		H2S Service	AM005WB0002
	7"	Standard Service	AM005WA0008
		H2S Service	AM005WB0008
Continuous Spinner	1.375"	Standard Service	AM005WA0003
		H2S Service	AM005WB0003
	1.688"	Standard Service	AM005WA0004
		H2S Service	AM005WB0004
	2.125"	Standard Service	AM005WA0007
		H2S Service	AM005WB0007

#### Accessories

Accessory Type	Part No.
Pelican Case Assembly	107625
Redress Kit Viton 90	107626
Redress Kit Aflas 7182B	107627
Redress Kit Chemraz 510	107628

#### Specifications

	Pressure	Temperature
Accuracy	0.022 % F.S.	0.25°C
Resolution	0.0003% F.S.	0.005°C
Drift	< 3 psi/year	< 0.1°C/year
Casing Collar Locator		
Detector Type	Electromagnetic	
Flowmeter		
Minimum Rotation	30 rpm	
Maximum Rotation	18,000 rpm	
Resolution	0.125 rps	
Memory		
Capacity	1.8 Million Samples	
Communcation Method	USB	