







#### Features

-  Fully Welded Construction
-  Hermetically Sealed
-  Dual Protection Metal to Metal Seal Design
-  Corrosion Resistant NACE MR0175
-  Dual Axis Vibration Sensor Option
  -  Capable Of Monitoring Pump Wear

Piezo Permanent - Inconel 718			
Pressure	Temperature	Wire Size	Part No.
750 psi	150°C	1/4"	104500
1,500 psi			104501
3,000 psi			104502
6,000 psi			104503
10,000 psi			104504
15,000 psi		1/8"	104506
750 psi			104507
1,500 psi			104508
3,000 psi			104509
6,000 psi			104510
10,000 psi			104511

Piezo Permanent With Vibration - Inconel 718			
Pressure	Temperature	Wire Size	Part No.
750 psi	150°C	1/4"	104512
1,500 psi			104513
3,000 psi			104514
6,000 psi			104515
10,000 psi			104516
15,000 psi		1/8"	104518
750 psi			104519
1,500 psi			104520
3,000 psi			104521
6,000 psi			104522
10,000 psi			104523

Specifications		
	Pressure	Temperature
<b>Accuracy Up To</b>	0.022% Full Scale	0.25 °C
<b>Resolution</b>	0.0003% Full Scale	0.005 °C
<b>Drift</b>	< 3 psi / year	< 0.1 °C / year
<b>Vibration Range</b>	+/- 50 g	