



Features

- ◆ Fully Welded Construction
- ◆ Hermetically Sealed
- ◆ Dual Protection Metal to Metal Seal Design
- ◆ Dual Axis Vibration Sensor Option
 - Capable Of Monitoring Pump Wear

Piezo Permanent - Stainless			
Pressure	Temperature	Wire Size	Part No.
750 psi	150 °C	1/4"	104476
1,500 psi			104477
3,000 psi			104478
6,000 psi			104479
10,000 psi			104480
15,000 psi			104481
750 psi		1/8"	104482
1,500 psi			104483
3,000 psi			104484
6,000 psi			104485
10,000 psi			104486
15,000 psi			104487

Piezo Permanent With Vibration - Stainless			
Pressure	Temperature	Wire Size	Part No.
750 psi	150 °C	1/4"	104488
1,500 psi			104489
3,000 psi			104490
6,000 psi			104491
10,000 psi			104492
15,000 psi			104493
750 psi		1/8"	104494
1,500 psi			104495
3,000 psi			104496
6,000 psi			104497
10,000 psi			104498
15,000 psi			104499

Specifications		
	Pressure	Temperature
Accuracy Up To	0.022% Full Scale	0.25 °C
Resolution	0.0003% Full Scale	0.005 °C
Drift	< 3 psi / year	< 0.1 °C / year
Vibration Range	+/- 50 g	