



### Features

- ✦ 200 °C Option
- ✦ 2 Million Sample Capacity
- ✦ Inconel 718 or MP35N – NACE MR0175
- ✦ Electron Beam Welded
- ✦ Modular Memory for Easy Field Replacement
- ✦ Fast Temperature Response
- ✦ Short Tool – Only 18" Long
- ✦ Can Quickly and Easily be Converted to SRO System

#### 0.75" OD Quartz Memory II - Inconel 718

Pressure	Temperature	Part No.
10,000 psi	150 °C	104605
10,000 psi	177 °C	105078
16,000 psi	150 °C	105036
16,000 psi	177 °C	105037
20,000 psi	177 °C	105038
20,000 psi	200 °C	105039
25,000 psi	177 °C	105040
25,000 psi	200 °C	105041

#### Accessory Type

Accessory Type	Part No.
Bullnose SS316	100402
Crossover 0.5-13 UNC SS316	100403
Crossover 0.25 NPT SS316	100404
Battery Barrel 2 X "AA" Inconel 718	100755
SRO Housing	105130
Pelican Case Assembly	100444
USB to Serial Converter Assembly	100682
Redress Kit Viton 90	100445
Redress Kit Aflas 7182B	100446
Redress Kit Chemraz 510	100447
Replaceable Memory Module 125 °C	105107
Replaceable Memory Module 177 °C	104599
Replaceable Memory Module 200 °C	105108
Replaceable SRO Module 150 °C	105132

#### Specifications

	Pressure	Temperature
<b>Accuracy</b>	0.020% F.S.	0.25 °C
<b>Resolution</b>	0.00006% F.S.	0.005 °C
<b>Drift</b>	< 3 psi / year	< 0.1 °C / year
<b>Capacity</b>	2 Million Samples	
<b>Communication Method</b>	USB	