







### Features

-  Super Seal Technology
  - 30,000 psi @ 1.25" OD
-  200 °C Option
-  Modular Memory Cartridge
-  2 Million Sample Capacity
-  Inconel 718 or MP35N – NACE MR0175
-  Fast Response

#### 1.25" OD Quartz Memory Tool - Inconel 718

Pressure	Temperature	Part No.
10,000 psi	150 °C	100711
16,000 psi	150 °C	100228
16,000 psi	177 °C	100229
16,000 psi	200 °C	100894
20,000 psi	177 °C	100230
20,000 psi	200 °C	100231
25,000 psi	177 °C	100232
25,000 psi	200 °C	100233
30,000 psi	200 °C	100234

#### Accessory Type

Accessory Type	Part No.
Replaceable Memory Module LTR 125 °C	104960
Replaceable Memory Module LTR 177 °C	104657
Replaceable Memory Module LTR 200 °C	104833
Welded Bullnose Inconel 718	102321
Welded Crossover 0.75-16 Inconel 718	102323
Crossover 0.25 NPT Inconel 718	100130
Battery Barrel 1 X "Sub CC" Inconel 718	100713
Battery Barrel 2 X "Sub CC" Inconel 718	101006
Replaceable SRO Module 150 °C	101864
SRO Housing Inconel 718	101819
Pelican Case Assembly	100235
USB To Serial Converter Assembly	100682
Redress Kit Viton 90	100908
Redress Kit Aflas	100237
Redress Kit Chemraz	100238

#### Specifications

	Pressure	Temperature
<b>Accuracy</b>	0.020% F.S.	0.25 °C
<b>Resolution</b>	0.00006% F.S.	0.005 °C
<b>Drift</b>	< 3 psi / year	< 0.1 °C / year
<b>Capacity</b>	2 Million Samples	
<b>Communication Method</b>	USB	