


Features

- ★ Value Priced
- ★ Fully Welded Construction
- ★ Hermetically Sealed
- ★ Dual Protection Metal to Metal Seal Design
- ★ Corrosion Resistant NACE MR0175
- ★ Dual Axis Vibration Sensor Option
 - Capable Of Monitoring Pump Wear



Low Temp Piezo Permanent - Inconel 718			
Pressure	Temperature	Wire Size	Part No.
750 psi	85 °C	1/4"	102470
1,500 psi			102472
3,000 psi			102473
6,000 psi			102474
10,000 psi			102475
15,000 psi			102476
750 psi		1/8"	102471
1,500 psi			102477
3,000 psi			102478
6,000 psi			102479
10,000 psi			102480
15,000 psi			102481

Low Temp Piezo Permanent With Vibration - Inconel 718			
Pressure	Temperature	Wire Size	Part No.
750 psi	85 °C	1/4"	101870
1,500 psi			101893
3,000 psi			101894
6,000 psi			101895
10,000 psi			101896
15,000 psi			101897
750 psi		1/8"	101878
1,500 psi			101898
3,000 psi			101899
6,000 psi			101900
10,000 psi			101901
15,000 psi			101902

Specifications		
	Pressure	Temperature
Accuracy Up To	0.022% Full Scale	0.25 °C
Resolution	0.0003% Full Scale	0.005 °C
Drift	< 3 psi / year	< 0.1 °C / year
Vibration Range	+/- 50 g	