

Memory Adapter Tool



Description

The Memory Adapter Tool (MAT) collects and records digital data from each sensor in a tool string. Unlike the Telemetry Tool (which transmits all data to a surface acquisition system), the memory adapter stores all data within its own, internal memory. A casing collar locator (CCL) is contained in the adapter, but a separate gamma ray is required in a tool string. The MAT tool requires a lithium battery pack in order to operate.

Memory Production Logging (MPL) is done using the MAT Job feature in the Premier Logging Suite. It is used to configure tool settings, upload and download settings and data, and manage information that is obtained from the memory adapter tool. MAT Job performs the following functions:

- Allows for configuration of the tool at surface (upload of program table, synchronization of tool and computer clocks, tool erase).
- Sets the program table, including the data acquisition rate.
- Allows tool string (sonde) selection.
- Time stamps the individual logging pass in a tabulated format.
- Retrieves data from the memory adapter tool at job completion.
- Merges time-stamped logging passes with depth and creates data files of individual passes.

Please refer to the Premier Acquisition Software page for more information on program features.

Main Features

- Collects digital data from connected downhole tools
- Lithium battery pack powers MAT and all tools in string
- Stores data withing 64MB internal memory core
- 1, 12.5, and 25 samples/sec recording rates per tool channel
- Data is downloaded into a computer via USB
- Software generates Premier Logging file
- CCL contained within tool body
- Perfect for use in remote or hazardous environments

Specifications

Specification	Details
OD	1.375 in (34.9 mm)
Length	44.9 in (1,140 mm)
Weight	10.8 lb (5 kg)
Pressure Rating	15,000 psi (103.5 MPa)
Memory Size	64 MB
Recording Rate(s)	1, 12.5, and 25 samples/sec

Configurations

Part Number	Specification	Temperature Rating
AM015WA0008	Standard Service	302°F (150°C)
106235	Standard Service High Temperature	350°F (177°C)
AM015WB0008	Sour Service	302°F (150°C)
106236	High Temperature Sour Service	350°F (177°C)

Lithium Battery Specifications

Specification	Details
Pack Length (complete assembly)	35.8 in (910 mm)
Capacity	13 Ah

Spare Parts

- Hex Socket Cap: SCC6-32SB01875
- Seal Kit: AM015RK0001
- Spring Pin: SP1/16SB050 (x2)

Accessories

- Standard Lithium Battery(165°C): AM015UU0006
- High Temperature Lithium Battery (180°C): 106285
- Battery De-Passivation Box: 106326
- 18V AC Adapter: AE309UU0001
- Portable Memory System: AE302UU0008

(Includes: Linewise System, Premier Software Suite, laptop, thermal printer, and rugged carrying case)

