

Smart Batteries

DataCan's battery packs are now available with capacity measurement circuits.

These new "smart battery packs" record the current draw from each lithium battery cell and give users an accurate measurement of the battery packs remaining life.

The recorded battery capacity can be read by DataCan's easy to use gauge software.

C - 6 Pin Lemo Connector

Size	Max Temp	Volts	Ahr	Part No.	Products
C	150°C	3.6	6.0	102056	1-1/4" Piezo (Standard, RTD, Welded III)
2 x C	150°C		12.0	104287	

C - Threaded Locking 6 Pin Lemo Connector

Size	Max Temp	Volts	Ahr	Part No.	Products
C	150°C	3.6	6.0	102069	1-3/8" Piezo (Welded)
2 x C	150°C		12.0	102073	

Sub CC - Threaded Locking 6 Pin Lemo Connector

Size	Max Temp	Volts	Ahr	Part No.	Products
Sub CC	150°C	3.6	10.0	102063	1-1/4" Quartz DXB
2 x Sub CC	150°C		12.0	102066	



1 x "C"
6 Pin Lemo



1 x "Sub CC"
Threaded Locking
6 Pin Lemo



1 x "C"
Threaded Locking
6 Pin Lemo

+1(281) 974-7010
+1(403) 352-2245

info@datacan.ca