



#### 1/8" OD Wire

- ✦ 316SS Armor
  - 0.024" Wall Triple Tube = 20,000psi
- ✦ Inconel 825 Armor
  - 0.024" Wall Triple Tube = 20,000psi
- ✦ Encapsulation (Optional)
  - Size
    - 0.25" Round
  - Material
    - Polypropylene = Standard
    - Santoprene
    - Rislun = Diesel Protection
- ✦ Insulation
  - Teflon = 200°C Max
- ✦ Conductor
  - 22 AWG
  - 18 AWG
  - 16 AWG

#### 1/4" OD Wire

- ✦ 316SS Armor
  - 0.028" Wall = 17,500psi
  - 0.035" Wall = 25,000psi
  - 0.049" Wall = 32,500psi
- ✦ Inconel 825 Armor
  - 0.028" Wall = 20,000psi
  - 0.035" Wall = 27,500psi
  - 0.049" Wall = 35,000psi
- ✦ Encapsulation (Optional)
  - Size
    - 11mm x 11mm
    - 0.375" Round
  - Material
    - Polypropylene = Standard
    - Santoprene
    - Rislun = Diesel Protection
- ✦ Insulation
  - Halar E = 100°C Max
  - Halar P = 150°C Max
  - Teflon = 200°C Max
- ✦ Conductor
  - 18 AWG
  - 16 AWG