

Batteries

AAA - 4 Pin Lemo Connector

Size	Max Temp	Volts	Ahr	Part No.	Products
AAA	150°C	3.6	0.7	104284	1/2" Piezo
	165°C		0.7	104287	

AA - 4 Pin Lemo Connector

Size	Max Temp	Volts	Ahr	Part No.	Products
AA	150°C	3.6	1.6	100408	3/4" Piezo (Standard, Welded, Accelerometer) 3/4" Quartz DXB 1" Quartz DXB
	165°C		1.6	100804	
	180°C		1.4	100805	
	200°C		1.2	100409	
2 x AA	150°C	3.6	3.2	100411	1" Side Pocket Geothermal 3/4" Inclinometer 3/4" Vibration
	165°C		3.2	100806	
	180°C		2.8	100807	
	200°C		2.4	100412	

AA - Threaded Locking 4 Pin Lemo Connector

Size	Max Temp	Volts	Ahr	Part No.	Products
2 x AA	150°C	3.6	3.2	105262	1-1/4" Burst
	165°C		3.2	105263	
	180°C		2.8	105264	

C - 4 Pin Lemo Connector

Size	Max Temp	Volts	Ahr	Part No.	Products
C	150°C	3.6	6.5	100671	1-1/4" Piezo (Standard, RTD, Welded III)
	165°C		5.5	100499	
	180°C		5.5	100500	
1 x CC	150°C	3.6	15.0	101010	
	165°C		14.0	100989	
	180°C		10.5	100814	



1 x "AAA"
4 Pin Lemo



1 x "AA"
4 Pin Lemo



1 x "C"
4 Pin Lemo

Batteries

C - Threaded Locking 4 Pin Lemo Connector						
Size	Max Temp	Volts	Ahr	Part No.	Products	
C	150°C	3.6	6.5	101268	1-3/8" Piezo (Welded) Production Logging Tools (Basic, Mini)	
	165°C		5.5	101269		
	180°C		5.5	101270		
	200°C		5.0	101271		
1 x CC	150°C		15.0	102362		1-1/4" Quartz DXB II
	165°C		14.0	102240		
	180°C		10.5	105234		
	200°C		9.0	105235		
2 x CC	150°C		30.0	102780	1-1/4" Quartz DXB II	
	165°C		28.0	102927		
	180°C		21.0	102928		
	200°C		18.0	102929		
3 x CC	150°C	45.0	102381	1-1/4" Quartz DXB II		
	165°C	42.0	102937			
	180°C	31.5	102938			
	200°C	27.0	102939			



1 x "C"
Threaded Locking
4 Pin Lemo



1 x "Sub CC"
Threaded Locking
4 Pin Lemo

Sub CC - Threaded Locking 4 Pin Lemo Connector						
Size	Max Temp	Volts	Ahr	Part No.	Products	
Sub CC	150°C	3.6	10.0	100808	1-1/4" Quartz DXB	
	165°C		9.0	100226		
	180°C		7.0	100885		
	200°C		6.5	100227		
2 x Sub CC	150°C		20.0	101660		1-1/4" Quartz DXB
	165°C		18.0	101000		
	180°C		14.0	102023		
	200°C		13.0	101001		

Batteries

C/D - 4 Pin Amphenol Connector					
Size	Max Temp	Volts	Ahr	Part No.	Products
2 x C	150°C	7.3	6.0	102376	Digital Clock
	165°C		5.5	103543	
3 x C	150°C	11.0	12.0	100639	2-3/8" Quick Shut In Tool 3-1/2" Quick Shut In Tool 4-1/2" Quick Shut In Tool
	165°C		11.0	100203	
3 x D	150°C		10.0	103586	
	165°C		10.0	103587	
	180°C		6.5	103588	

D - Logger Battery Pack					
Size	Max Temp	Volts	Ahr	Part No.	Products
2 x D	85°C	3.6	34.0	101472	Wellhead Logger Surface Logger



3 x "C"
4 Pin Amphenol